



TECHNICAL CHARACTERISTIC	
NOMINAL SIZE	80 mm
NOMINAL PRESSURE	1.6MPa
BODY TEST PRESSURE	2.4MPa
SEALING TEST PRESSURE	1.76MPa
APPLICATION TEMP	EPDM ≤ 80°C
MEDIUM	WATER
MAIN MATERIAL	GGG50

21	OUTLET BOLT	4	SS316	ASTM A276	SS316
20	OUTLET	1	SS316	ASTM A276	SS316
19	"O" RING	1	NBR	AS1646	NBR
18	Plastic Cap	1	Plastic		
17	DOWN WASHER	1	C48600	AS1565	C48600
16	UP WASHER	1	C48600	AS1565	C48600
15	STEM CAP BOLT	1	SS316	ASTM A276	SS316
14	STEM CAP	1	GGG50	AS1831	BS500/7
13	DUSTPROOF COVER	1	EPDM	AS1646	EPDM
12	SEALING PART	1	NBR/C48600		
11	"O" RING	1	NBR	AS1646	NBR
10	TOP BONNET BOLT	3	SS316	ASTM A276	SS316
9	CLANG FLANGE	1	SS316	ASTM A276	SS316
8	BONNET	1	GGG50	AS1831	BS500/7
7	THRUST COLLAR	1	SS304	ASTM A276	SS304
6	"O" RING	1	NBR	AS1646	NBR
5	BODY BONNET BOLT	3	SS316	ASTM A276	SS316
4	STEM	1	1Cr17Ni2	ASTM A276	BS431S29
3	STEM NUT FOR LOOSE STOPPER	1	C48600	AS1565	C48600
2	DISC RUBBER	1	EPDM	AS1646	EPDM
2	DISC	1	GGG50	AS1831	BS500/7
1	BODY	1	GGG50	AS1831	BS500/7

MARKS	NAME	NO. PIECES	MATERIAL	STANDARD	MINIMUM GRADE																																																							
<table border="1"> <tr> <td>PROTECCION SUPERFICIAL</td> <td colspan="2">BETA FLUID SOLUTIONS</td> <td colspan="3">Underground Fire Hydrant</td> </tr> <tr> <td>ESPECIFICACIONES APLICABLES</td> <td colspan="2"> </td> <td> <table border="1"> <tr> <th>PROYECT</th> <th>NUMBRE</th> <th>FORMA</th> <th>FECHA</th> <th>ESCALAS</th> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> </table> </td> <td colspan="2"></td> </tr> <tr> <td colspan="3">DENOMINACION</td> <td colspan="3">ASSEMBLY DRAWING</td> </tr> <tr> <td colspan="3">NUMERO</td> <td colspan="3">80 BFH41X1-16Q-1</td> </tr> <tr> <td colspan="3">IND. MODIFICATION</td> <td colspan="3">01</td> </tr> </table>						PROTECCION SUPERFICIAL	BETA FLUID SOLUTIONS		Underground Fire Hydrant			ESPECIFICACIONES APLICABLES			<table border="1"> <tr> <th>PROYECT</th> <th>NUMBRE</th> <th>FORMA</th> <th>FECHA</th> <th>ESCALAS</th> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> </table>	PROYECT	NUMBRE	FORMA	FECHA	ESCALAS				SEP. 13					SEP. 13					SEP. 13					SEP. 13				DENOMINACION			ASSEMBLY DRAWING			NUMERO			80 BFH41X1-16Q-1			IND. MODIFICATION			01		
PROTECCION SUPERFICIAL	BETA FLUID SOLUTIONS		Underground Fire Hydrant																																																									
ESPECIFICACIONES APLICABLES			<table border="1"> <tr> <th>PROYECT</th> <th>NUMBRE</th> <th>FORMA</th> <th>FECHA</th> <th>ESCALAS</th> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SEP. 13</td> <td></td> </tr> </table>	PROYECT	NUMBRE	FORMA	FECHA	ESCALAS				SEP. 13					SEP. 13					SEP. 13					SEP. 13																																	
PROYECT	NUMBRE	FORMA	FECHA	ESCALAS																																																								
			SEP. 13																																																									
			SEP. 13																																																									
			SEP. 13																																																									
			SEP. 13																																																									
DENOMINACION			ASSEMBLY DRAWING																																																									
NUMERO			80 BFH41X1-16Q-1																																																									
IND. MODIFICATION			01																																																									

Technical specifications

- Design standard: BS 750:2006 TYPE- II;
- Flange: AS4087 DN100 class16, drilled as AS2129 Table-D, DN80 & DN90.